


Medium ESP
DUCT (50/100Pa)



HW-BA116ABK YR-E17A HW-BA101ABT YR-E16B YR-HRS01
*1. HW-BA116ABK, YR-E17A and HW-BA101ABT have built-in infrared signal receiver. YR-E16B no such function

Medium ESP
DUCT (50/100Pa)

Model/Indoor unit			AD052MJERAB	AD072MJERAB	AD092MJERAB	AD122MJERAB	AD162MJERAB	AD182MJERAB	AD242MJERAB	AD282MJERAB	AD302MJERA	AD382MJERA	AD482MJERA	AD542MJERA
Capacity	Cooling	kBtu/h	5.1	7.5	9.5	12.3	15.3	19.1	24.2	27.3	30.7	38.2	47.8	54.6
		kW	1.5	2.2	2.8	3.6	4.5	5.6	7.1	8	9	11.2	14	16
	Heating	Btu/h	5.8	8.5	10.9	13.6	17.1	21.5	27.3	30.7	34.1	44.4	55.6	61.4
		kW	1.7	2.5	3.2	4	5	6.3	8	9	10	13	16.3	18
Electrical Parameters	Power supply	Ph/V/Hz	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
	Air flow (H)	m ³ /h	630/510/424	630/510/424	630/510/424	630/510/424	740/550/442	980/840/760	1174/1080/960	1174/1080/960	1500/1180/930	1700/1300/900	2000/1700/1250	2000/1700/1250
Performance	Sound pressure level(H/M/L)	dB(A)	35/33/31	35/33/31	35/33/31	35/33/31	35/33/31	36/34/32	40/37/34	42/38/34	42/38/34	42/39/35	43/40/35	43/40/35
	Sound power level(H/M/L)	dB(A)	39/37/35	39/37/35	39/37/35	39/37/35	39/37/35	40/38/36	44/41/38	46/42/38	46/42/38	46/33/39	47/44/39	47/44/39
Installation	External dimensions(W/D/H)	mm	700/700/248	700/700/248	700/700/248	700/700/248	700/700/248	1100/700/248	1100/700/248	1100/700/248	1100/700/248	1500/700/248	1500/700/248	1500/700/248
	Shipping dimensions(W/D/H)	mm	932/835/280	932/835/280	932/835/280	932/835/280	932/835/280	1332/835/280	1332/835/280	1332/835/280	1332/835/280	1698/857/305	1698/857/305	1698/857/305
	Net/Shipping weight	kg	27/32	27/32	27/32	27/32	28.5/33.5	36.8/43.5	37/43.4	37/43.6	39.4/45.4	48.3/56.5	51.3/59.5	51.3/59.5
	Refrigerant liquid pipe	mm	6.35	6.35	6.35	6.35	6.35	6.35	9.52	9.52	9.52	9.52	9.52	9.52
	Refrigerant gas pipe	mm	9.52	9.52	9.52	12.7	12.7	12.7	15.88	15.88	15.88	15.88	15.88	15.88
	Static Pressure(Standard/Max.)	Pa	50/100	50/100	50/100	50/100	50/100	50/100	50/100	50/100	50/100	50/100	50/100	50/100
Drain pump	O-optional,S-standard,W-without		S	S	S	S	S	S	S	S	S	S	S	S
Controller	Wired(Optional)	/	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT
		/	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B
		/	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A
		/	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK
	Infrared(Optional)	/	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01



50/100Pa
Only 248mm thick



Built-in drain pump
All module can realize 50/60Hz